

DEMiPlus₁₈₀

SCHEDA TECNICA OSMOSI

Dimensioni (LxHxP): cm 11x48,5x38,5

Peso: 11 kg

Alimentazione: 230 V - 50 Hz

Assorbimento: 190 W

Pressione d'ingresso (Min-Max): 0,2 - 0,35 MPa (2 - 3,5 bar)

Pressione di esercizio: 1 - 1,1 MPa (10 - 11 bar)

Motore: 180 W

Pompa: 300 l/h in ottone con by-pass

Pre-filtrazione: filtro WCF BASIC 250 HF (attacco rapido, 180 l/h, durata 5.000 litri, fibra cava + carbon block 0,15 micron). Il pre-filtro deve essere fissato sulla spalla interna del mobile sottolavello

Membrane osmosi: 2 membrane 180 GPD TFM 1812

Produzione H₂O liscia: 80 - 90 l/h a 25° C - 0,3 MPa (3 bar)

Lampada UV: 11 W, interna



Dispositivi di sicurezza installati:

- allarme antiallagamento
- allarme esaurimento giorni/litri pre-filtro e membrane osmosi
- blocco impianto in caso di mancanza d'acqua

Il led rimane acceso fisso o lampeggia per segnalare l'esaurimento del pre-filtro o eventuali anomalie. Il buzzer emetterà un segnale acustico.

Posizionamento:

di facile installazione, posizionandolo sia nel sotto-lavello in orizzontale o in verticale, che sotto il mobile della cucina.

Dotazione per il montaggio:

testata pre-filtro con attacco rapido, piedini in gomma adesivi, raccordi, tubi di collegamento, staffa di scarico, clip di sicurezza e cavo di alimentazione.

Pre-filtri opzionali:

WCF BASIC 350 HF, durata 10.000 litri

WCF BASIC 500 HF, durata 15.000 litri

DemiPlus180



Via Mezzabarba 5/B - 20084 Lacchiarella (MI) - Italia
Tel: +39 02 900 33 145 Fax: +39 02 900 300 59
email: info@sigroup.info WWW.SIGROUP.INFO



DEMiPlus₁₈₀

OSMOSIS DATA SHEET

Dimensions (WxHxD): cm 11x48.5x38.5

Weight: 11 kg

Power supply: 230 V - 50 Hz

Absorption: 190 W

Inlet pressure (Min-Max): 0,2 - 0,35 MPa (2 - 3,5 bar)

Operative pressure: 1 - 1,1 MPa (10 - 11 bar)

Engine: 180 W

Pump: 300 l/h in brass with by-pass

Pre-filtration: filter WCF BASIC 250 HF (quick connection, 180 l/h, lifetime 5,000 liters, hollow fiber + carbon block 0.15 micron). The pre-filter has to be fixed to the inner shoulder of the under-sink

Osmosis membrane: 2 membranes 180 GPD TFM 1812

H₂O production: 80 - 90 l/h at 25° C - 0,3 MPa (3 bar)

UV lamp: 11 W, internal



Safety devices installed:

- anti-flooding alarm
- days/liters depletion alarm for pre-filter and osmosis membranes
- machine block in case of lack of water

The led remains lit or blinks to indicate the exhaustion of the pre-filter or any anomalies. The buzzer will emit an acoustic signal.

Positioning:

easy to install, positioning it either under-sink horizontally or vertically, or under-plinth of the kitchen.

Installation kit included:

pre-filter head with quick coupling, adhesive rubber feet, fittings, connecting pipes, drainage bracket, safety clips and power cord.

Optional pre-filters:

WCF BASIC 350 HF, lifetime 10,000 liters

WCF BASIC 500 HF, lifetime 15,000 liters

DemiPlus180



Via Mezzabarba 5/B - 20084 Lacchiarella (MI) - Italia
Tel: +39 02 900 33 145 Fax: +39 02 900 300 59
email: info@sigroup.info WWW.SIGROUP.INFO

